

U. S. Corrosion Technologies, LLC  
P. O. Box 551625  
Dallas, Texas 75355-1625  
(972) 271-7361 Fax: (972) 278-9721

# AERO-GLIDE™

## Safety Data Sheet

### 1. IDENTIFICATION

**Product Name:** AERO-GLIDE™  
**Product Numbers:** 65301, 65302, 65303, 65304, 65305  
**Product Type and Use:** Cleaner / Polish / Protective Coating  
**Manufacturer:** U.S. Corrosion Technologies, LLC  
2638 National Drive, Garland, TX 75041  
Telephone: 972-271-7361 Fax: 972-278-9721  
**Contact:**  
**Emergency Telephone:** CHEMTREC® Australia (Sydney) +(61)-290372994

**Poisons Information Centre:** Australia: 13 11 26  
**Distributor in Australia:** Applied Industrial Technologies Pty Ltd  
22 Stamford Road  
Oakleigh VIC  
Australia 3166  
PO Box 1011, Huntingdale VIC 3166  
Tel: +613 9567 8700  
AH: +61 427 740 927  
Fax: +613 9567 8733

### 2. HAZARDS IDENTIFICATION

#### Hazard Classification

##### Health Hazard(s)

Skin Irritation Category 2  
Eye Irritation Category 2B  
STOT-SE Category 3

##### Physical Hazard(s)

Flammable Liquids Category 4

##### Hazard(s) not otherwise classified

Aspiration Hazard Category 1

#### Labeling

**Signal Word:** DANGER  
**Pictograms:** Exclamation Mark, Health Hazard

#### Statements of Hazard

##### Hazard Statements

Combustible liquid  
Causes skin and eye irritation  
May cause drowsiness or dizziness  
May be fatal if swallowed and enters airway

##### Precautionary Statements

Store in a well-ventilated place. Keep container cool and tightly closed. Keep away from flames and hot surfaces – No smoking. In case of fire: Use carbon dioxide, dry chemical, or foam to extinguish. Use only outdoors or in a well-ventilated area. Avoid breathing mist or vapors. Wear eye protection and protective gloves. Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse. Do not swallow. Dispose of contents and container in accordance with applicable regulations.  
If on skin: Wash with plenty of water. If skin irritation occurs: get medical advice. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell. If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately call a physician or poison control center.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Percent by Wt.
Naphtha (petroleum), hydrotreated heavy	64742-48-9	25-30*

\* Exact percentage of composition has been withheld as a trade secret

### 4. FIRST AID MEASURES

**General Advice:** Causes skin and eye irritation. Avoid skin and eye contact. Use with adequate ventilation. Avoid breathing mist or vapors. Prolonged or repeated inhalation may cause dizziness and drowsiness. Do not swallow.

**Inhalation:** Remove from exposure area. Remove to fresh air. Give artificial respiration if not breathing. Get medical attention.

**Skin Contact:** Wipe excess from skin; remove contaminated clothing. Wash with soap and water. Seek medical attention if irritation persists.

**Eye Contact:** Flush eyes with plenty of water for 15 minutes while holding eyelids open. Seek medical attention if irritation persists.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Immediately call a physician or poison control center.

### 5. FIRE FIGHTING MEASURES

**Extinguishing Media:** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Suitable:** Carbon Dioxide, Dry Chemical, and Foam

**Unsuitable:** Alcohol, Alcohol based solutions, any other media not listed above.

**Fire Fighting Procedures:** As in any fire, wear self-contained breathing apparatus, pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**Unusual Fire and Explosion Hazards:** Solvent vapors are heavier than air and may travel to distant, low lying sources of ignition and may ignite and explode.

**Hazardous Combustion/ Decomposition Products:** Oxides of carbon.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions / Protective Equipment / Emergency Procedures:** Use caution as spills may be slippery. Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition and take precautionary measures against static discharges.

**Methods and materials for containment and cleaning up:** Do not flush into surface water or sanitary sewer system. Dike and contain spillage. Soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite). Use clean non-sparking tools to collect absorbed material and transfer to a properly labeled container for disposal according to applicable regulations.

## 7. HANDLING AND STORAGE

### HANDLING

**Precautions for Safe Handling:** Avoid skin and eye contact. Use with adequate ventilation. Avoid breathing mist or vapors. Follow all SDS/label precautions even after container is empty due to residue.

### STORAGE

**Conditions to avoid:** Store in a cool, dry, well-ventilated place in the original container. Keep container tightly closed when not in use. Avoid excess heating, high temperatures, sparks, hot surfaces, open flames and all other sources of ignition.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE LIMITS

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Component	ACGIH		OSHA		STEL ppm	STEL mg/m3
	TLV ppm	TLV mg/m3	PEL ppm	PEL mg/m3		
Naphtha (petroleum), hydrotreated heavy	171	1200	Not Est.	Not Est.	Not Est.	Not Est.

**Engineering Controls:** Use outdoors or with local exhaust ventilation. Ensure adequate ventilation, especially in confined areas.

### Personal Protection

**Respiratory Protection:** None required under normal use conditions. In case of insufficient ventilation and for exposures above occupational exposure limits wear a NIOSH approved air purifying respirator with organic vapor cartridge.

**Hand / Skin Protection:** Wear impermeable gloves such as neoprene or nitrile rubber gloves.

**Eye / Face Protection:** Safety glasses with side-shields. An eyewash station should be available to the area of use.

**General Hygiene Measures:** Avoid skin and eye contact. Always wash hands and face before eating, drinking or smoking. Remove and wash contaminated clothing before re-use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Opaque	<b>Autoignition Temperature:</b>	Not established
<b>Physical State:</b>	Non-viscous liquid	<b>Volatile by volume (%):</b>	29
<b>Odor:</b>	Hydrocarbon	<b>Vapor Density (Air=1) :</b>	>1
<b>Color:</b>	Light brown	<b>Evaporation Rate (BuAc=1) :</b>	0.87
<b>Viscosity, cSt @ 40°C:</b>	Not established	<b>Vapor Pressure, mmHg @23°C:</b>	>1 mmHg
<b>cSt @ 104°C:</b>	64.7	<b>Solubility in water:</b>	Emulsifiable
<b>pH:</b>	Not applicable	<b>Octanol/Water Partition:</b>	Not established
<b>Boiling Point/ Range:</b>	>237°F / 114°C	<b>VOC Content (g/L) (%):</b>	(290) 29
<b>Melting Point:</b>	Not established	<b>Specific Gravity @ 22.2°C:</b>	0.98
<b>Flash Point:</b>	143°F / 62°C	<b>Pour Point:</b>	Not established
<b>Method:</b>	Tag Closed Cup	<b>Non-volatile by Volume (%):</b>	71
<b>Lower Explosive Limit, vol %:</b>	0.7	<b>Dielectric Strength (KV):</b>	Not applicable
<b>Upper Explosive Limit, vol %:</b>	5.3		

## 10. STABILITY AND REACTIVITY

**Stability:** Stable at ambient temperatures.

**Conditions to Avoid:** Avoid high temperatures, sparks, open flame and all other sources of ignition.

**Hazardous Polymerization:** Will not occur.

**Materials to Avoid:** Bases, acids and strong oxidizing materials.

## 11. TOXICOLOGICAL INFORMATION

### Acute Toxicity

**Product Information:** Not established

**Ingredient Information:** Not established

### Acute Effects

**Signs and Symptoms of Overexposure:** Skin Irritation, Eye Irritation, Coughing, Sneezing, Dizziness, Drowsiness

**Inhalation:** May cause coughing and sneezing. Prolonged and repeated inhalation may cause nausea, dizziness and drowsiness.

**Skin Contact:** Prolonged or repeated contact may cause irritation in sensitive individuals.

**Eye Contact:** May cause stinging, tearing and redness.

**Ingestion:** May cause nausea, vomiting and diarrhea. Ingestion and subsequent vomiting may result in aspiration of the product into the lungs resulting in chemical pneumonitis, pneumonia and pulmonary edema.

**Primary Route(s) of Exposure:** Skin, Eyes, Inhalation

**Primary Route(s) of Entry:** Inhalation, Ingestion

**Target Organs:** Skin, Eyes, Central Nervous System

**Chronic Effects:** None known

**Carcinogenicity:** Not established

**Medical Conditions Aggravated by Exposure:** May aggravate existing skin, eye and respiratory conditions such as asthma and dermatitis.

## 12. ECOLOGICAL INFORMATION

**Product Data:** Not established  
**Ingredient Data:** Not established  
**Elimination Information:** Not established

## 13. DISPOSAL CONSIDERATIONS

**Product:** Dispose of in accordance with applicable regulations.  
**Container:** Empty remaining contents. Empty containers should be taken for local recycling, recovery or waste disposal. Empty containers may contain residues. Do not cut, weld or grind empty containers.

## 14. TRANSPORT INFORMATION

### Road Transport

**DOT Hazard Class:** Not regulated

### Sea Transport

**IMDG/GGV See Class:** Not regulated

### Air Transport

**ICAO/IATA Class:** Not regulated

## 15. REGULATORY INFORMATION

### **U.S. Federal Regulations**

**Toxic Substances Control Act (TSCA):** All components are included on the Inventory

**Superfund Amendments and Reauthorization Act (SARA) Title III:**

Immediate Hazard	Delayed Hazard	Fire Hazard	Pressure Hazard	Reactivity Hazard
Yes	No	Yes	No	No

## 16. OTHER INFORMATION

**Prepared by:** U.S. Corrosion Technologies, LLC Technical Services Department  
**Revision Date:** 12/10/2018      **Supersedes Date:** 11/15/2016  
**Revision Indicator:** v 1.1 New OSHA 2012 SDS

National Fire Protection Association (704)  
Health: 1      Flammability: 2      Reactivity: 0      Other: -

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results and assume no liability for damage incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Final determination of suitability of the chemical and application of such products is the sole responsibility of the user. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or any other nature are made hereunder with respect to the information contained herein or the chemical to which the information refers. It is the sole responsibility of the user to comply with all applicable Federal, State and Local Laws and Regulations. Any questions with regards to information contained herein should be referred to: U. S. Corrosion Technologies, LLC (972) 271-7361.