ASPHALT REMOVER

ECONOMICAL AND EFFECTIVE WAY TO CLEAN ASPHALT & TAR

PRODUCT HIT POINTS

- Bio-based
- Nonhazardous
- Contains no chlorinated or hydrocarbon-based solvents
- Environmentally responsible and biodegradable
- Nonflammable (flash point more than 250° F)
- Can be diluted up to 5:1 with water (one part Asphalt Remover to five parts water) to clean lighter accumulations of asphalt and tar.

DESCRIPTION

Asphalt Remover is a bio-based formula made using natural plant oils to create a product that offers all the cleaning power you need without resorting to the harsh, environmentally hazardous chemicals used by most commercial tar and asphalt removers.

Spray or wipe-on a light coating of Asphalt Remover, and within seconds, the product will begin to liquify hydrocarbon-based contaminants such as asphalt, tar and greasy road film. Once liquified, the contaminants can be easily removed by wiping off or conventional washing.



SUGGESTED APPLICATIONS

Asphalt dump beds • Asphalt and other roadworking equipment

 Cleaning and degreasing engines
 Degreasing tractors, spray rigs and earth moving equipment
 Fleet operators of trucks, trailers, haulers and tankers











PROPERTIES

Appearance: Physical State:

Odor: Color:

Viscosity, cSt @ 40°C:

cSt @ 104°C:

pH:

Boiling Point/ Range:

Melting Point: Flash Point:

Method:

Lower Explosive Limit, vol %: Upper Explosive Limit, vol %:

Transparent

Nonviscous liquid

Citrus Brown

Not established Not established

8.5

176°C / 349°F Not established 70°C / 158°F

Tag Closed Cup

0.7 6.1 **Autoignition Temperature:** 261°C / 502°F

Percent Volatile by volume: 21
Vapor Density (Air=1): 3.9
Evaporation Rate (BuAc=1): 0.2
Vapor Pressure, mmHg @23°C: <2

Solubility in water:

Octanol/Water Partition (log Pow)

d-limonene 4.23 VOC Content (%) (g/L): 21 (210) Specific Gravity @ 22.2°C: 0.88

Pour Point:

Non-volatile by Volume (%):

Dielectric Strength (KV):

Not established 75 Not applicable

Emulsifiable

PRODUCT CODES		
Part Number	UPC Code	Product Description
31104	761866 31104 3	1 gallon
31105	761866 31105 0	5 gallon
31102	-	30 gallon
31101	-	55 gallon

