

CorrosionX

All-Safe



Product Description

Time release concrete remover. Turns hardened concrete into "sand" for easy removal. Leading edge technology for removal of dried concrete.

Can be left to do concrete removal overnight without damaging the paint on your truck ! Spray it on and agitate with a brush. All-Safe will remove concrete like a traditional acid-based product. Leave it on and All-Safe will convert concrete into mud for easy removal.

Safe for use on trucks, forms, and all your concrete equipment.

All Safe is **non-hazardous** to ship in any quantity, which makes it an excellent option for jobs needing small quantities (as the product can ship with any common carrier. Can be used on sensitive substances such as aluminium and magnesium surfaces.

Removes up to 3 mm of concrete.

- Safe on paint, steel, aluminum, magnesium, rubber, plywood and fiberglass – as well as your skin!
- No harmful fumes or harsh acids
- Biodegradable
- Non-hazardous to ship and use
- Works hand-in-hand with “Silispray”, non stick coating made for working smart, not hard !

Application Suggestion

Spray or brush on. Agitate to speed up the process or simply leave the product to do the job.

Ideal for

Concrete trucks and pumps.

Tools in the concrete industry or

At home when working with concrete

Direction of use

Instant removal

Apply full strength or diluted up to 3:1 with water depending on concrete build up. The proper dilution ratio depends upon the thickness of concrete to be removed and how long it has been on the surface. Agitate with a soft bristle brush to facilitate quicker removal.

Time release / Dipping

Apply liberally to any residual dried concrete or submerge item in a poly, plastic or rubber dip tank. Steel tanks may also be used if they are coated with epoxy paint or lined with vinyl. Let the product sit for at least 5 minutes – or longer in the case of thicker deposits. Product can be left on overnight to minimize cleanup effort. If left on overnight, re-wet surface with product prior to rinsing, brushing, etc.

Rinse

Once concrete has been transformed into mud, it can be easily removed by rinsing with water, pressure washing, brushing, or wiping off with a rag or towel.

Safety brief / precautions

Wear gloves and eye protection when working with AllSafe. Do not swallow product. Keep away from children.

For full briefing please see SDS sheet.