U. S. Corrosion Technologies, LLC

P. O. Box 551625

Dallas, Texas 75355-1625

(972) 271-7361 Fax: (972) 278-9721

BULK

NavGuard™ II Safety Data Sheet

1. IDENTIFICATION

Product Name: NavGuard™ II

Product Numbers: 30203, 30204, 30205, 30207, 30208

Product Type and Use: Corrosion Inhibitor / Moisture Displacer / Lubricant

Manufacturer:U.S. Corrosion Technologies, LLC2638 National Drive, Garland, TX 75041Contact:Telephone: 972-271-7361Fax: 972-278-9721

Emergency Telephone: CHEMTREC® USA (800) 424-9300

Outside US +1 (703) 527-3887

Poisons Information Centre: Australia: 13 11 26

Distributor in Australia: Applied Industrial Technologies Pty Ltd

22 Stamford Road Oakleigh VIC Australia 3166

PO Box 1011, Huntingdale VIC 3166

Tel: +613 9567 8700 AH: +61 427 740 927 Fax: +613 9567 8733

2. HAZARDS IDENTIFICATION

Hazard Classification

Health Hazard(s)

Skin Irritation Category 2
Eye Irritation Category 2B
STOT-SE Category 3

Physical Hazard(s)

Flammable Liquids Category 4 **Hazard(s) not otherwise classified**Aspiration Hazard Category 1

Labeling

Signal Word: DANGER

Pictograms: Exclamation Mark, Heath Hazard

Statements of Hazard Hazard Statements

Combustible liquid Causes skin and eye irritation

May cause respiratory irritation, drowsiness or dizziness

May be fatal if swallowed and enters airways

Precautionary Statements

Store in a well-ventilated place. Keep cool. Keep away from flames and hot surfaces – No smoking. In case of fire: Use carbon dioxide, dry chemical or foam to extinguish. Use only outdoors or in a well-ventilated area. Avoid breathing mist and vapors. Wear eye protection and protective gloves. Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse. Dispose of contents and container in accordance with applicable regulations.

If on skin: Wash with plenty of water. If skin irritation occurs: get medical advice.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.

If swallowed: Immediately call a doctor or poison center. Do NOT induce vomiting.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Percent by Wt.
Heavy hydrotreated naphthenic petroleum distillates	64742-52-5	25-30*
Naphthalenesulfonic acid, dinonyl-, calcium salt (2:1)	57855-77-3	15-20*
Naphtha (petroleum), hydrotreated heavy	64742-48-9	25-30*
Calcium carbonate	471-34-1	1-5*
Hexylene glycol	107-41-5	1-5*

^{*} Exact percentage of composition has been withheld as a trade secret

4. FIRST AID MEASURES

General Advice: Causes skin and eye irritation. Avoid skin and eye contact. Aspiration hazard; do not swallow. May cause lung damage. Use with adequate ventilation. Avoid breathing mist or vapor. Prolonged or repeated inhalation may cause dizziness and drowsiness. Keep container closed.

Inhalation: Remove from exposure area. Remove to fresh air. Give artificial respiration if not breathing. Get medical attention. **Skin Contact:** Wipe excess from skin; remove contaminated clothing. Wash with soap and water. Seek medical attention if irritation persists.

Eye Contact: Flush eyes with plenty of water for 15 minutes while holding eyelids open. Seek medical attention if irritation persists. **Ingestion:** Rinse mouth. Do NOT induce vomiting. Immediately call a physician or poison control center.

5. FIRE FIGHTING MEASURES

Extinguishing Media: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Suitable: Carbon Dioxide, Dry Chemical, and Foam

Unsuitable: Alcohol, Alcohol based solutions, any other media not listed above.

Fire Fighting Procedures: As in any fire, wear self-contained breathing apparatus, pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Unusual Fire and Explosion Hazards: Solvent vapors are heavier than air and may travel to distant, low lying sources of ignition and may ignite and explode.

Hazardous Combustion/ Decomposition Products: Oxides of carbon, sulfur, calcium, magnesium and phosphorous

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions / Protective Equipment / Emergency Procedures: Use caution as spills may be slippery. Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition and take precautionary measures against static discharges.

Methods and materials for containment and cleaning up: Do not flush into surface water or sanitary sewer system. Dike and contain spillage. Soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite). Use clean non-sparking tools to collect absorbed material and transfer to a properly labeled container for disposal according to applicable regulations.

7. HANDLING AND STORAGE

HANDLING

Precautions for Safe Handling: Avoid skin and eye contact. Use with adequate ventilation. Avoid breathing mist or vapors. Follow all SDS/label precautions even after container is empty due to residue. **STORAGE**

Conditions to avoid: Store in a cool, dry, well-ventilated place in the original container. Keep container tightly closed when not in use. Avoid excess heating, high temperatures, sparks, hot surfaces, open flames, and all other sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMITS						
	ACGIH		OSHA			
Component	TLV ppm	TLV mg/m3	PEL ppm	PEL mg/m3	STEL ppm	STEL mg/m3
Heavy hydrotreated naphthenic petroleum distillates	Not est.	5	Not est.	5	Not est.	10
Naphthalenesulfonic acid, dinonyl-, calcium salt (2:1)	Not est.	Not est.	Not est.	Not est.	Not est.	Not est.
Naphtha (petroleum), hydrotreated heavy	171	1200	Not est.	Not est.	Not est.	Not est.
Calcium carbonate	Not est.	Not est.	Not est.	10 total/ 5 resp.	Not est.	Not est.
Hexylene glycol	Not est.	5	10	Not est.	25	125

Engineering Controls: Use outdoors or with local exhaust ventilation. Ensure adequate ventilation, especially in confined areas. Personal Protection

Respiratory Protection: None required under normal use conditions. In case of insufficient ventilation and for exposures above occupational exposure limits wear a NIOSH approved air purifying respirator with organic vapor cartridge.

Hand / Skin Protection: Wear impermeable gloves such as neoprene or nitrile rubber gloves. Gauntlets and apron may be worn depending on the extent and duration of exposure.

Eye / Face Protection: Safety glasses with side-shields. An eyewash station should be available to the area of use.

General Hygiene Measures: Avoid skin and eye contact. Always wash hands and face before eating, drinking or smoking. Remove and wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Physical State: Odor: Color: Viscosity, cSt @ 40°C:	Transparent Non-viscous liquid Hydrocarbon Amber/Lt brown Not established	Autoignition Temperature: Volatile by volume (%): Vapor Density (Air=1): Evaporation Rate (BuAc=1): Vapor Pressure, mmHg @23°C:	Not established 41 >1 <0.01 >1 mmHg Insoluble
cSt @ 104°C: pH: Boiling Point/ Range: Melting Point: Flash Point: Method: Lower Explosive Limit, vol %: Upper Explosive Limit, vol %:	64.7 Not applicable >450°F / 232°C Not established 65°C / 149°F Cleveland Open Cup 0.7 5.3	Solubility in water: Octanol/Water Partition: VOC Content g/l (%): Specific Gravity @ 22.2°C: Pour Point: Non-volatile by Volume (%): Dielectric Strength (KV):	Not established 290 (29) 0.896 Not established 59 28

10. STABILITY AND REACTIVITY

Stability: Stable at ambient temperatures.

Conditions to Avoid: Avoid high temperatures, sparks, open flame, and all other sources of ignition.

Hazardous Polymerization: Will not occur.

Materials to Avoid: Bases, acids, amines and oxidizing materials.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product Information: Not established **Ingredient Information:** Not established

Acute Effects

Signs and Symptoms of Overexposure: Skin Irritation, Eye Irritation, Coughing, Sneezing, Dizziness, Drowsiness

Inhalation: May cause coughing and sneezing. Prolonged and repeated inhalation may cause nausea, dizziness and

drowsiness.

Skin Contact: Prolonged or repeated contact may cause mild irritation in sensitive individuals.

Eye Contact: May cause stinging, tearing and redness.

Ingestion: May cause nausea, vomiting and diarrhea. Ingestion and subsequent vomiting may result in aspiration of the

product into the lungs resulting in chemical pneumonitis, pneumonia, and pulmonary edema.

Primary Route(s) of Exposure: Eyes, Inhalation Primary Route(s) of Entry: Inhalation, Ingestion

Target Organs: Skin, Eyes, Central Nervous System, Lungs

Chronic Effects: None known Carcinogenicity: Not established

Medical Conditions Aggravated by Exposure: May aggravate existing skin, eye and respiratory conditions such as asthma and

dermatitis.

12. ECOLOGICAL INFORMATION

Product Data: Not established
Ingredient Data: Not established
Elimination Information: Not established

13. DISPOSAL CONSIDERATIONS

Product: Dispose of in accordance with applicable regulations.

Container: Empty remaining contents. Empty containers should be taken for local recycling, recovery or waste disposal. Empty

containers may contain residues. Do not cut, weld or grind empty containers.

14. TRANSPORT INFORMATION

Road Transport
DOT Hazard Class: 3
UN-No.: UN1268

Proper Shipping Name: Petroleum distillates, n. o. s. (>119 gallon - < 119 Not Regulated)

Sea Transport

IMDG/GGV See Class: Not regulated

Air Transport

ICAO/IATA Class: Not regulated

15. REGULATORY INFORMATION

U.S. Federal Regulations

Toxic Substances Control Act (TSCA): All components are included on the Inventory

Superfund Amendments and Reauthorization Act (SARA) Title III:

Immediate	Delayed	Fire	Pressure	Reactivity
Hazard	Hazard	Hazard	Hazard	Hazard
Yes	No	Yes	No	No

16. OTHER INFORMATION

Prepared by: U.S. Corrosion Technologies, LLC Technical Services Department Issue Date: 10/11/2016 Supersedes Date: Not applicable

Revision Indicator: v 1.0 New SDS

National Fire Protection Association (704)

Health: 1 Flammability: 2 Reactivity: 0 Other:

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results and assume no liability for damage incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Final determination of suitability of the chemical and application of such products is the sole responsibility of the user. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or any other nature are made hereunder with respect to the information contained herein or the chemical to which the information refers. It is the sole responsibility of the user to comply with all applicable Federal, State and Local Laws and Regulations. Any questions with regards to information contained herein should be referred to: U. S. Corrosion Technologies, LLC (972) 271-7361.