

# REELX<sup>®</sup>

## DESCRIPTION

ReelX is the new, hi-tech, extreme pressure optimized reel lubricant that virtually eliminates wear, disrupts existing corrosion and prevents new corrosion or rust from forming. ReelX is the perfect choice for all spinning and casting reels.

ReelX sticks to metal like a magnet, so it cannot be easily displaced by pressure, friction or moisture. It lubricates under extreme loads and high temperatures. And not only does ReelX lubricate better, because it is bonded to metal on the molecular level, it lasts many times longer than conventional fishing reel lubricants!

REELX WILL OUTPERFORM ANY OTHER LUBRICANT ON A FISHING REEL – PERIOD.



## PROPERTIES

|                                      |                    |                                    |                 |
|--------------------------------------|--------------------|------------------------------------|-----------------|
| <b>Appearance:</b>                   | Transparent        | <b>Autoignition Temperature:</b>   | Not established |
| <b>Physical State:</b>               | Non-viscous liquid | <b>Volatile by volume (%):</b>     | 4               |
| <b>Odor:</b>                         | Fresh scent        | <b>Vapor Density (Air=1) :</b>     | 5.9             |
| <b>Color:</b>                        | Greenish-brown     | <b>Evaporation Rate (BuAc=1) :</b> | <1              |
| <b>Viscosity, cSt @ 40°C:</b>        | 33.2               | <b>Vapor Pressure, mmHg @20°C:</b> | <0.05           |
| <b>cSt @ 100°C:</b>                  | 7.0                | <b>Solubility in water:</b>        | Insoluble       |
| <b>pH:</b>                           | Not applicable     | <b>Octanol/Water Partition:</b>    | Not established |
| <b>Boiling Point/ Range:</b>         | > 421°F / 216°C    | <b>VOC Content g/l (%):</b>        | 0 (0)           |
| <b>Melting Point:</b>                | Not established    | <b>Specific Gravity @15.6°C:</b>   | 0.895           |
| <b>Flash Point:</b>                  | 143°C / 290°F      | <b>Pour Point:</b>                 | -22°F / -30°C   |
| <b>Method:</b>                       | Cleveland Open Cup | <b>Non-volatile by Volume (%):</b> | 96              |
| <b>Lower Explosive Limit, vol %:</b> | Not Est.           | <b>Dielectric Strength (KV):</b>   | 30              |
| <b>Upper Explosive Limit, vol %:</b> | Not Est.           |                                    |                 |

## PRODUCT CODES

| Part Number | UPC Code       | Product Description          |
|-------------|----------------|------------------------------|
| 77000       | 761866 77000 0 | 1 fl oz precision applicator |



# REELX<sup>®</sup>

PERFORMANCE REEL TREATMENT

## GREASE

### DESCRIPTION

ReelX Grease is the new, hi-tech, synthetic, extreme-pressure optimized reel grease developed for all spinning and casting reels. Used in conjunction with ReelX<sup>®</sup> fishing reel oil, ReelX Grease blocks moisture intrusion, reduces wear, disrupts existing corrosion and prevents new corrosion or rust from forming.

ReelX Grease combines our top rated marine grease with an additive package containing the same revolutionary Polar Bonding technology found in CorrosionX<sup>®</sup> products and additional extreme pressure additives to make your fishing reels achieve their ultimate performance.



### PROPERTIES

|                                      |                    |                                    |                 |
|--------------------------------------|--------------------|------------------------------------|-----------------|
| <b>Appearance:</b>                   | Opaque             | <b>Autoignition Temperature:</b>   | Not established |
| <b>Physical State:</b>               | Non-viscous liquid | <b>Volatile by volume (%):</b>     | 2.4             |
| <b>Odor:</b>                         | Fresh scent        | <b>Vapor Density (Air=1) :</b>     | 5.9             |
| <b>Color:</b>                        | Aqua blue          | <b>Evaporation Rate (BuAc=1) :</b> | <1              |
| <b>Viscosity, cSt @ 40°C:</b>        | ND                 | <b>Vapor Pressure, mmHg @20°C:</b> | <0.05           |
| <b>cSt @ 100°C:</b>                  | ND                 | <b>Solubility in water:</b>        | Insoluble       |
| <b>pH:</b>                           | Not applicable     | <b>Octanol/Water Partition:</b>    | Not established |
| <b>Boiling Point/ Range:</b>         | > 421°F / 216°C    | <b>VOC Content g/l (%):</b>        | 5.2(0.6)        |
| <b>Melting Point:</b>                | Not established    | <b>Specific Gravity @15.6°C:</b>   | 0.88            |
| <b>Flash Point:</b>                  | 143°C / 290°F      | <b>Pour Point:</b>                 | ND              |
| <b>Method:</b>                       | Cleveland Open Cup | <b>Non-volatile by Volume (%):</b> | 97.6            |
| <b>Lower Explosive Limit, vol %:</b> | Not Est.           | <b>Dielectric Strength (KV):</b>   | ND              |
| <b>Upper Explosive Limit, vol %:</b> | Not Est.           |                                    |                 |

### PRODUCT CODES

| Part Number | UPC Code       | Product Description          |
|-------------|----------------|------------------------------|
| 77960       | 761866 77960 7 | 1 fl oz precision applicator |

